

431DST.4.01-I738



Pendant linear downlights with symmetrical light distribution.
Linear fixture in 575mm length, width of 62mm and height of 85mm.
Protection rating against dust and moisture: complete IP66.
Protection rating for resistance to harmful mechanical impacts: IK10.
Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
Highly efficient linear printed circuit board.
Protection polycarbonate diffuser in 4mm.
Interior optic to control the light.
Built-in driver.
Electronic options for lighting control: DALI/DSI.
Anti-condensation device.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screw.
Ceiling-mounted with adjustable steel wire suspension (1m) and electrical wire. Different suspension length on request.
The electric cable inlet is on one end of the luminaire. Luminaires can also be supplied with two cable inlets, one on each side, for serial installation, reference F3.L4.DST.
The driver is on the inside of the fixture.
Passive temperature management.

Light source power: 16 W
Fixture power: 17.21 W
Constant Current: 350 mA
Luminous flux of the light source: 2650lm
Luminous flux of the fixture: 2254lm
CRI: 80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 43°
LOR: 85%
Average Service Life: 50000h
LED reliability: >60000h L80B10
Photobiological safety group: 1
Cd/Klm: 815
Luminous efficacy: 131 lm/W
Imax: 2161 Cd

This product contains a light source of energy efficiency class C


Electronic Equipment

S: On/Off
D: DALI-2/DSI switchDIM/corridorFUNCTION


*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com