# RAINA 100 IP40 Recessed linear downlights



	151RNA.1-I730
	IP40 650° IP40 650°   577 x 58mm
	Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 585mm length and in a width of 68mm.
	Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser. Highly efficient linear printed circuit board.
	Built-in driver, included. Electronic options for lighting control: DALI-2.
	Passive temperature management. Ceiling-mounted using steel support with screws. End caps must be ordered separately, reference M5.E0068.
	It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.Q0068.
34 [34]	Light source power: 11 W   Imax=427 Cd   n=100.0% V M V Ø VLUX   103°     Luminaire connected power: 12.08 W   1   2.5   427
585	Constant Current: 250 mA Light source luminous flux: 1900lm Luminaire luminous flux: 1140lm
	CRI: 80 Colour Temperature: 2700K
10	Chromaticity Tolerance: MacAdam 3 Beam Angle: 103° LOR: 60%
<sup>F</sup>	Average Service Life: 50000h LED reliability: >60000h L80B10
2_	<b>UGR:</b> <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20%   50%   70% Luminaire spacing = 0.45m
75	Photobiological safety group: 1 Luminaire efficiency: 94 lm/W This product contains a light source of energy efficiency class D
M5.E0068 M5.Q0068	Electronic Equipment S: On/Off D: DALI-2/switchDIM/corridorFUNCTION
	*Add the suffix <b>-S</b> , <b>-D</b> after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

## 5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

### **Contact** T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com