

RAINA 200

IP40 Frameless recessed linear downlights









251RNA.1-I726









Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using steel support with screws.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.P0055.

lmax=283 Cd

110

η=100.0% ▼ M ▼ Ø ▼ LUX

1 2.5 283

2 5.0 71

4 10.0

7.5

12.5 11.3

17.7

103°

Light source power: 6 W

Luminaire connected power: 7.1 W

Constant Current: 150 mA Light source luminous flux: 1260lm Luminaire luminous flux: 755lm

CRI: 80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°

LOR: 60%

Average Service Life: 50000h LED reliability: >60000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.4m

Photobiological safety group: 1 Luminaire efficiency: 106 lm/W

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com