

M5.E0055


M5.P0055

251RNA.1-I731



IP40

650°



Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Frameless linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using steel support with screws.

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.P0055.

Light source power: 11 W

Luminaire connected power: 12.08 W

Constant Current: 250 mA

Light source luminous flux: 1960lm

Luminaire luminous flux: 1175lm

CRI: 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°

LOR: 60%

Average Service Life: 50000h

LED reliability: >60000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.45m

Photobiological safety group: 1

Luminaire efficiency: 97 lm/W

This product contains a light source of energy efficiency class C

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION


*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com
www.rovasi.com