

RAINA 400

IP20 Pendant linear downlights

ROVASI
Positive Lighting










M5.E0055 M5.GR M5.U

451RNA.1-I726

IP20 | 650º | +ELEC | +RAL | +MODULAR

Pendant linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
Linear fixture in 569mm length and in a width of 55mm.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Opal polycarbonate diffuser.
Highly efficient linear printed circuit board.
Built-in driver, included.
Electronic options for lighting control: DALI/DSI.
Passive temperature management.
Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.
End caps must be ordered separately, reference M5.E0055.
Ceiling rose and electrical wire must be ordered separately, reference M5.GR3 [on/off] o M5.GR5 [DALI].
It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.U.

Light source power: 6 W
Fixture power: 7.1 W
Constant Current: 150 mA
Luminous flux of the light source: 1260lm
Luminous flux of the fixture: 755lm
CRI: 80
Colour Temperature: 5000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 103º
LOR: 60%
Average Service Life: 50000h
LED reliability: >60000h L80B10
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.4m
Photobiological safety group: 1
Luminous efficacy: 106 lm/W
This product contains a light source of energy efficiency class C




▼M	▼Ø	▼LUX	103º
1	2.5	283	
2	5.0	71	
3	7.5	31	
4	10.0	17.7	
5	12.5	11.3	

Electronic Equipment
S: On/Off
D: DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes
1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**