# RAINA 600 IP40 Wall-mounted linear fixtures





# 651RNA.1-I732



Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser. Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.


Wall mounted by mounting brackets.


Light source power: 11 W

End caps must be ordered separately, reference M5.E0055.

It is possible to combine different lengths to create customized design. The connection accessory must be ordered separately, reference M5.U.







M5.E0055

M5.U

Luminaire connected power: 12.08 W Constant Current: 250 mA Light source luminous flux: 2050lm Luminaire luminous flux: 1085lm CRI: 80 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 103° LOR: 60% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: 19 under the below indicated parameters

dam 3

Imax=460 Cd η=100.0% ▼M ▼Ø ▼LUX 103° 1 2.5 460 2 5.0 115 180 3 7.5 51 270 29 4 10.0 5 12.5 18.4

Photobiological safety group: 1 Luminaire efficiency: 90 lm/W This product contains a light source of energy efficiency class C

## **Electronic Equipment**

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.45m

S: On/Off D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

# 5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com