RAINA 800

IP40 Projectors



η=100.0% ▼ M

165

220

1 2.5 283

2 5.0

3 7.5 31

4 10.0 17.7

5


▼Ø ▼LUX

12.5 11.3


71

103°



















Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 569mm length and in a width of 55mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management.

Ceiling or wall installation with adjustable fixing brackets.

Light source power: 6 W Fixture power: 7.1 W Constant Current: 150 mA

Luminous flux of the light source: 1260lm Luminous flux of the fixture: 667lm

CRI: 80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 103°


LOR: 60%

Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.4m

Photobiological safety group: 1 Luminous efficacy: 94 lm/W

This product contains a light source of energy efficiency class C



Electronic Equipment

S: On/Off

D: DALI-2/DSI/switchDIM

There are accessories available for dimming devices.

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346 BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

info@rovasi.com www.rovasi.com

T. +34 93 881 35 12 T. +34 93 881 37 13