



101FLC.1.02-I867



Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient lighting.

Neutral cylindrical body in diameter 150mm.

Protection rating against dust and moisture: complete IP54.

White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.

Powder painted aluminium body available in assorted finishes, customized RAL under request.

Intermediate tempered frosted glass .

Integral driver supplied.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through aluminium heat sink and the fixture body itself.

Mounting to the ceiling plate with two securing holes. Cable entry from the top of the luminaire.

Light source power: 11 W

Luminaire connected power: 12.61 W

Constant Current: 350 mA

Light source luminous flux: 1730lm

Luminaire luminous flux: 1021lm

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 63°

LOR: 59%

Average Service Life: 50000h

LED reliability: 50000h L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.5m

Photobiological safety group: 1

Cd/Klm: 819

Luminaire efficiency: 81 lm/W

This product contains a light source of energy efficiency class E

Electronic Equipment

S: On/Off (AC/DC)


D: DALI-2/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com