FLOCCUS Surface mounted downlights

150



65°

+ INSTAL +RAL <u>*<u></u></u> IP54 IK05 850° Surface-mounted downlight with symmetrical light distribution to achieve an effective task or ambient liahtina. Neutral cylindrical body in diameter 150mm. Protection rating against dust and moisture: complete IP54. White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option. Powder painted aluminium body available in assorted finishes, customized RAL under request. Intermediate tempered frosted glass . Integral driver supplied. Electronic options for lighting control: DALI/DSI. Passive temperature management: heat dissipation flows through aluminium heat sink and the fixture body itself. Mounting to the ceiling plate with two securing holes. Cable entry from the top of the luminaire. Light source power: 17 W lmax=1444 Cd η=100.0% ▼M ▼Ø ▼LUX 210 Fixture power: 18.33 W 1 1.28 1444 Constant Current: 500 mA 361 2 2.6 Luminous flux of the light source: 2990lm 500 Luminous flux of the fixture: 1764lm 3 3.9 160 750 **CRI:** >80 1000 4 90 5.1 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 5 6.4 58 Beam Angle: 63° LOR: 59% Average Service Life: 50000h LED reliability: 50000h L90B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.6m Photobiological safety group: 1 Cd/Klm: 819 Luminous efficacy: 96 lm/W This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off D: DALI-2/DSI switchDIM/corridorFUNCTION *Add the suffix -S, -D after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

101FLC.1.02-I871

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com