


102CML.1.02-l864



Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting.
Neutral cylindrical body in diameter 190mm.
Protection rating against dust and moisture: complete IP54.
White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.
Powder painted aluminium body available in assorted finishes, customized RAL under request.
Intermediate tempered frosted glass .
Integral driver supplied.
Electronic options for lighting control: DALI-2.
Passive temperature management: heat dissipation flows through aluminium heat sink and the fixture body itself.
Delivered with 1meter powder painted metal rod as standard.
Mounted to the ceiling by cylindrical ceiling rose.

Light source power: 11 W
Luminaire connected power: 12.61 W
Constant Current: 350 mA
Light source luminous flux: 2040lm
Luminaire luminous flux: 1469lm
CRI: >80
Colour Temperature: 3000K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 80°
LOR: 72%
Average Service Life: 50000h
LED reliability: 50000h L90B10
UGR: <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.35m
Photobiological safety group: 1
Cd/Klm: 614
Luminaire efficiency: 116 lm/W
This product contains a light source of energy efficiency class D



Electronic Equipment


S: On/Off (AC/DC)
D: DALI-2/switchDIM/corridorFUNCTION
B: Bluetooth-Casambi

*Add the suffix **-S**, **-D**, **-B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346
BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 www.rovasi.com