


CUMULUS EVOLUTION

Pendant downlights

ROVASI
Positive Lighting



102CEV.1.02-I863



IP20

IK05

850°



Pendant downlight with symmetrical light distribution to achieve an effective task or ambient lighting.
Neutral cylindrical body in diameter 190mm.
White painted aluminium reflector. Sandblasted metalized aluminium reflector available as option.
Powder painted aluminium body available in assorted finishes, customized RAL under request.
Intermediate tempered frosted glass .
Integral driver supplied.
Electronic options for lighting control: DALI-2.
Passive temperature management: heat dissipation flows through aluminium heat sink and the fixture body itself.
Suspended 1 meter by three steel cords. Transparent electrical wire.
Mounted to the ceiling by cylindrical ceiling rose.
Optional complete IP54 if the fixture is supplied with black wire.

Light source power: 11 W

Fixture power: 12.61 W

Constant Current: 350 mA

Luminous flux of the light source: 1960lm

Luminous flux of the fixture: 1411lm

CRI: >80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 80°

LOR: 72%

Average Service Life: 50000h

LED reliability: 50000h L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70%

Luminaire spacing = 0.35m

Photobiological safety group: 1

Cd/Klm: 614

Luminous efficacy: 112 lm/W

This product contains a light source of energy efficiency class D

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION



*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 24.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com
www.rovasi.com