## KAUTTA 200



## IP40 Frameless recessed linear downlights

1	231KTA.1-I724
	IP40       650°       +RAL
	<ul> <li>Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.</li> <li>Frameless linear fixture in 568mm length and in a width of 44mm.</li> <li>Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.</li> <li>PMMA optics for controlling and directing the light.</li> <li>Highly efficient linear printed circuit board.</li> <li>Accessories available to create customized linear systems.</li> <li>Built-in driver, included.</li> <li>Electronic options for lighting control: DALI-2.</li> </ul>
<u>-</u> 568	Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. Other options available: Frameless recessed. Surface mounted. Pendant. Wall-mounted. Projector. It is possible to combine different lengths and junction modules in different ways to create customized design.
	Light source power: 6 W Fixture power: 7.1 W Constant Current: 150 mA Luminous flux of the light source: 1200lm Luminous flux of the fixture: 1118lm CRI: 80 Colour Temperature: 3000K
5 []]44	Chromaticity Tolerance: MacAdam 3 Beam Angle: 43°
568	LOR: 93% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20%   50%   70% Luminaire spacing = 0.3m Photobiological safety group: 1 Cd/KIm: 704 Luminous efficacy: 157 Im/W Imax: 846 Cd This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off D: DALL 9 (switch DIM (serrider FUNCTION)
	<ul> <li>D: DALI-2/switchDIM/corridorFUNCTION</li> <li>*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.</li> </ul>
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable
AL 1	

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.04.2024]
5 years guarantee

**CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

## Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com