

## 331KTA.1-I725




IP40

650°



Surface mounted linear fixtures with symmetrical light distribution to achieve an effective accent, task or general lighting.  
 Linear fixture in 568mm length and in a width of 44mm.  
 Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.  
 PMMA optics for controlling and directing the light.  
 Highly efficient linear printed circuit board.  
 Accessories available to create customized linear systems.  
 Built-in driver, included.  
 Electronic options for lighting control: DALI-2.  
 Passive temperature management.  
 Ceiling-mounted using cleats.  
 Other options available:  
 Recessed.  
 Frameless recessed.  
 Pendant.  
 Wall-mounted.  
 Projectors.  
 It is possible to combine different lengths and junction modules in different ways to create customized design.

**Light source power:** 6 W  
**Luminaire connected power:** 7.1 W  
**Constant Current:** 150 mA  
**Light source luminous flux:** 1260lm  
**Luminaire luminous flux:** 1170lm  
**CRI:** 80  
**Colour Temperature:** 4000K  
**Chromaticity Tolerance:** MacAdam 3  
**Beam Angle:** 43°  
**LOR:** 93%  
**Average Service Life:** 50000h  
**LED reliability:** >60000h L80B10  
**UGR:** <19 under the below indicated parameters  
 Room dimensions X=4H/8H  
 Reflectance 20% | 50% | 70%  
 Luminaire spacing = 0.3m  
**Photobiological safety group:** 1  
**Cd/Klm:** 704  
**Luminaire efficiency:** 165 lm/W  
**Imax:** 886 Cd  
**This product contains a light source of energy efficiency class C**



## Electronic Equipment

S: On/Off



D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix **-S**, **-D** after the reference to indicate your electronic equipment choice.

## Finishes

**2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

## Upgradeable, Replaceable, Repairable



## Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

## 5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

## ROVASI S.L.

Ronda de la Font Grossa, 15  
 Pol. Ind. La Gavarra  
 08540 Centelles | Barcelona  
 Spain

## Contact

T. +34 93 881 35 12    info@rovasi.com  
 T. +34 93 881 37 13    www.rovasi.com