

# KAUTTA 800

## **IP40 Projectors**









### 833KTA.1-I751



IP40 650°



Linear projectors with symmetrical light distribution to achieve an effective accent, task or general

Linear fixture in 848mm length and in a width of 44mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Imax=1233 Cd

η=93.4% ▼ M ▼ Ø ▼ LUX

2 1.58 308

3

4 3.2 77

0.79 1232

3.9 49

137 2.4

43°

PMMA optics for controlling and directing the light.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management.

Ceiling or wall installation with adjustable fixing brackets.

Other options available:

Recessed.

Frameless recessed.

Surface-mounted.

Pendant.

Wall-mounted.

Light source power: 10 W Fixture power: 10.66 W Constant Current: 150 mA

Luminous flux of the light source: 1750lm Luminous flux of the fixture: 1627lm

**CRI:** 80

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 43° **LOR:** 93%

Average Service Life: 50000h LED reliability: >60000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1

**Cd/Klm:** 704

Luminous efficacy: 153 lm/W

Imax: 1231 Cd

This product contains a light source of energy efficiency class  $\, \mathsf{D} + \mathsf{C} \,$ 

#### **Electronic Equipment**

D: DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

Spain

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13