TIRET 200

IP40 Frameless recessed linear downlights





75



259TRT.1-I636











Frameless recessed linear downlights with symmetrical light distribution to achieve an effective task or

Linear fixture in 2806mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board. Accessories available to create customized linear systems.

Built-in driver, included. Tunable White: 2700K - 6500K.

Electronic options for lighting control: DALI/DSI.

3 hours battery available as option.

Passive temperature management.

Ceiling-mounted using galvanized steel support with screws.

It is possible to combine different lengths and junction modules in different ways to create customized

Light source power: 154 W Fixture power: 154 W

Luminous flux of the light source: 15000lm Luminous flux of the fixture: 8700lm

CRI: >90

Colour Temperature: 2700K - 6500K

Beam Angle: 84°

Average Service Life: 50000h Photobiological safety group: 1

This product contains a light source of energy efficiency class F

lmax=3950 Cd η=99.9% ▼ M ▼ Ø ▼ LUX 1.79 3950 2 3.6 987 1500 3 439 5.4 4 7.1 247 8.9

Electronic Equipment

T: DALI-2/DSI SwitchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13