
TIRET 400 IP20 Pendant linear downlights





5		
]40
la		
	846	

453TRT.1-I615



Pendant linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 846mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included. Tunable White: 2700K - 6500K.


Electronic options for lighting control: DALI/DSI.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspensoin (1m) and transparent electrical wire. Different suspensoin length on request.

It is possible to combine different lengths and junction modules in different ways to create customized systems.

Light source power: 38.6 W Fixture power: 38.6 W Luminous flux of the light source: 4500lm Luminous flux of the fixture: 2610lm CRI: >90 Colour Temperature: 2700K - 6500K Beam Angle: 84° Average Service Life: 5000h Photobiological safety group: 1



This product contains a light source of energy efficiency class F

Electronic Equipment

T: DALI-2/DSI SwitchDIM/ColourSwitch

*Add the suffix -T after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com