# TIRET 600

## IP40 Wall-mounted linear fixtures
















Linear fixture in 566mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser. Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management. Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized

lmax=550 Cd

400

η=100.0% ▼ M ▼ Ø ▼ LUX

1 2.0 550


2 4.1 138

3

4 8.2

5 10.2 22 91°

34



Luminous flux of the light source: 1960lm Luminous flux of the fixture: 1235lm

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 91°

**LOR:** 63%

Average Service Life: 50000h LED reliability: >72000h L80B10 UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.6m

Photobiological safety group: 1

**Cd/Klm:** 443

Luminous efficacy: 102 lm/W

Imax: 868 Cd

This product contains a light source of energy efficiency class C

### **Electronic Equipment**

D: DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable







LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona

info@rovasi.com

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact

www.rovasi.com