HORIZON 200



IP20 Frameless recessed linear downlights

		I	221HRN.1-19)77						
			IP20 6	50° +RAL	577 x 53mm	2.49Kg				
			Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Frameless linear fixture in 576mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2.							
			It is possible to combine different lengths and junction modules in different ways to create customized design.							
L	576]65	Light source pow Luminaire connect Constant Current	cted power: 1	3.88 W	lmax=359	7 Cd	ŋ=100.0% ▼ M 1	VØ VLUX 0.56 3597	31°
			Light source lumin Luminaire lumino CRI: 80 Colour Temperat Chromaticity Tole Beam Angle: 31° LOR: 97% Average Service	inous flux: 18 ius flux: 1746 ure: 4000K erance: MacAd Life: 50000h	m dam 3	X	1400 2100 2800 3500	2 3 4 5	1.11 899 1.67 400 2.2 225 2.8 144	
4			LED reliability: >5 UGR: <19	54000h L80B1()					
F	576]50	Photobiological s Cd/KIm: 2060 Luminaire efficien Imax: 3708 Cd This product com	12 6 lm/W		y efficiency c	class C			
Electronic Equipment S: On/Off D: DALI-2/switchDIM/corridorFUNCTION										
		*Add the suffix -S , -D after the reference to indicate your electronic equipment choice.								
			Finishes 2: RAL9005: Jet Black	k, 4: RAL7016: Ar	nthracite Grey, 7: R/	AL9006: White A	luminium,	1: RAL9010:	Pure White	
			Upgradeable, Replaceable, Repairable							
					airable					

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com