

# HORIZON 200

## IP20 Frameless recessed linear downlights









## 281HRN.1-I986













Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting.

Linear frameless fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optic to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management.

Ceiling-mounted using steel support with screws.

Pre-wiring of 35cm cable 3x1mm2.

It is possible to combine different lengths and junction modules in different ways to create customized

max=2581 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 2.8 424

3 4.2

4 5.6 106

1.41 1696

7.1

188

Light source power: 20 W Fixture power: 23.25 W Constant Current: 700 mA

Luminous flux of the light source: 3210lm Luminous flux of the fixture: 2664lm

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: ASY°

**LOR:** 83%

Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1

Cd/Klm: 974

Luminous efficacy: 115 lm/W

Imax: 3127 Cd

This product contains a light source of energy efficiency class C

## **Electronic Equipment**

S: On/Off
D: DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

## Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.**

Spain

### Contact

T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

T. +34 93 881 35 12