
# HORIZON 100

## IP20 Recessed linear downlights









121HRN.1-I980













max=3099 Cd

η=100.0% ▼M ▼Ø ▼LUX

2

0.56 3099

> 2.2 194

775 1.11

344 1.67 3

Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 602mm length and in a width of 78mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI/DSI.

Passive temperature management.

Ceiling-mounted using steel support with spring clamps for easy installation...

Pre-wiring of 35cm cable 3x1mm2.

It is possible to combine different lengths and junction modules in different ways to create customized

Light source power: 10 W Fixture power: 13.88 W Constant Current: 350 mA

Luminous flux of the light source: 1550lm Luminous flux of the fixture: 1504lm

**CRI:** 90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31°

**LOR:** 97%

Average Service Life: 50000h LED reliability: >54000h L80B10

**UGR:** <19

Photobiological safety group: 1

**Cd/Klm:** 2060

Luminous efficacy: 108 lm/W

Imax: 3193 Cd

This product contains a light source of energy efficiency class D

#### **Electronic Equipment**

D: DALI-2/DSI switchDIM/corridorFUNCTION

\*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 19.04.2024]



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.** 

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona

T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

Contact

T. +34 93 881 35 12