## HORIZON 300



IP20 Surface mounted linear downlights

	381HRN.1-I980	
	IP20         650°         +RAL         ▲           2.22Kg         2.22Kg	
	Recessed surface mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear fixtures in 576mm length and in a width of 50mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using cleats. It is possible to combine different lengths and junction modules in different ways to create customized design.	
]65	Light source power: 10 W	lmax=1246 Cd η=100.0% ▼ M ▼ Ø ▼LUX 67°
4	Luminaire connected power: 13.88 W Constant Current: 350 mA Light source luminous flux: 1550lm Luminaire luminous flux: 1287lm CRI: 90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: ASY° LOR: 83% Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1 Cd/Klm: 974	200         1         1.41         819           400         2         2.8         205           900         3         4.2         91           400         4         5.6         51           1000         5         7.1         33
]50	Luminaire efficiency: 93 lm/W Imax: 1510 Cd	
576 This product contains a light source of energy efficiency class D		fficiency class D
	Electronic Equipment D: DALI-2/switchDIM/corridorFUNCTION *Add the suffix -D after the reference to indicate your electronic equipment choice.	
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL90	006: White Aluminium, <b>1:</b> RAL9010: Pure White
	Upgradeable, Replaceable, Repairable	

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

**5 years guarantee EALC CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.** Ronda de la Font Grossa, 15

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com