HORIZON 700

IP20 Wall-mounted linear fixtures double emission





721HRN.1-I976









Wall-mounted linear downlights or uplights with symmetrical light distribution to achieve an effective task or general lighting. Double light emission: up and down.

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in Driver, separate switching: up and down.

Electronic options for lighting control: DALI-2 (for downlight position only).

Passive temperature management. Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized

Imax=3341 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1

4 2.2

0.56 3341

209

1.12 835

1.68

2.8 134 31°



576

_____]50

Light source power: 10 W

Luminaire connected power: 13.88 W

Constant Current: 350 mA Light source luminous flux: 1680lm Luminaire luminous flux: 1630lm

CRI: 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 31° **LOR:** 97%

Average Service Life: 50000h LED reliability: >54000h L80B10

UGR: <19

Photobiological safety group: 1

Cd/Klm: 2060

Luminaire efficiency: 117 lm/W

Imax: 3461 Cd

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable







LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13