
HORIZON 600

IP20 Wall-mounted linear fixtures









681HRN.1-I980



IP20 650°





Wall mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent

Linear fixture in 576mm length and in a width of 50mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optic to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management. Wall mounted by mounting brackets.

It is possible to combine different lengths and junction modules in different ways to create customized design.

Imax=1246 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1

2 2.8 205

3

4 5.6

5 7.1 33

1.41 819

51

67°

Light source power: 10 W

Luminaire connected power: 13.88 W

Constant Current: 350 mA Light source luminous flux: 1550lm Luminaire luminous flux: 1287lm

CRI: 90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: ASY°

LOR: 83%

Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1

Cd/Klm: 974

Luminaire efficiency: 93 lm/W

Imax: 1510 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix **-D** after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13