## BARIS 200



IP54 Frameless recessed linear downlights

	251BRS.1-I728
	IP54         IK08         650°         +RAL
	<ul> <li>Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.</li> <li>Frameless linear fixture in 568mm length and in a width of 44mm.</li> <li>Protection rating against dust and moisture: complete IP54.</li> <li>Protection rating of resistance to harmful mechanical impacts: IK08.</li> <li>Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.</li> <li>Opal polycarbonate diffuser.</li> <li>Highly efficient linear printed circuit board.</li> <li>Built-in driver, included.</li> <li>Electronic options for lighting control: DALI/DSI.</li> <li>Passive temperature management.</li> <li>Ceiling-mounted using steel support with screws.Pre-wiring of 35cm cable 3x1mm2.</li> <li>Accessory for serial installation, reference F3.L2.BRS.</li> </ul>
· · ]78	Light source power: 6 W Imax=218 Cd η=100.0% ▼ M ▼ Ø ▼LUX 100°
568 568 ]44	Fixture power: 7.1 W Constant Current: 150 mA Luminous flux of the light source: 1035lm Luminous flux of the fixture: 549lm CRI: 90 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 100° LOR: 53% Average Service Life: 5000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20%   50%   70% Luminous efficacy: 77 lm/W Imax: 413 Cd This product contains a light source of energy efficiency class D Electronic Equipment S: On/Off D: DALI-2/DSI switchDIM/corridorFUNCTION
	*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.04.2024]

## 5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.**

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

## Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com