
BARIS 600

IP54 Wall mounted linear fixtures









651BRS.1-I728



IK08 IP54







Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general

Linear fixture in 568mm length and in a width of 44mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

lmax=218 Cd

120

η=100.0% ▼ M ▼ Ø ▼ LUX

1 2.4 218

2 4.8 54

3 7.2

4 9.6 13.6

> 12.0 8.7

100°

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Wall mounted by mounting brackets.

Accessory for serial installation, reference F3.L6.BRS.

Light source power: 6 W

Luminaire connected power: 7.1 W

Constant Current: 150 mA

Light source luminous flux: 1035lm Luminaire luminous flux: 549lm

CRI: 90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 96°

LOR: 53%

Average Service Life: 50000h LED reliability: >60000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.55m

Photobiological safety group: 1

Cd/Klm: 399

Luminaire efficiency: 77 lm/W

Imax: 413 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com