

# BARIS 100

## IP54 Recessed linear downlights









### 151BRS.1-I724









lmax=253 Cd

η=100.0% ▼ M ▼ Ø ▼ LUX

1 2.4 253

2 4.8 63

3 7.2 28

4 9.6 15.8

> 12.0 10.1

100°

Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 586mm length and in a width of 58mm.

Protection rating against dust and moisture: complete IP54.

Protection rating of resistance to harmful mechanical impacts: IK08.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal polycarbonate diffuser.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using steel support with screws.Pre-wiring of 35cm cable 3x1mm2.

Accessory for serial installation, reference F3.L1.BRS.

Light source power: 6 W

Luminaire connected power: 7.1 W

Constant Current: 150 mA

Light source luminous flux: 1200lm Luminaire luminous flux: 637lm

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 100°

**LOR:** 53%

Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: 19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.55m

Photobiological safety group: 1

Cd/Klm: 399

Luminaire efficiency: 90 lm/W

Imax: 480 Cd

This product contains a light source of energy efficiency class C

#### **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.**

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13