BARIS 100 IP54 Recessed linear downlights



	161BRS.1-I736
	IP54 IK08 650° +RAL Image: S74 x 47mm Image: S74 x 47mm
	 Wall or ceiling mounted recessed linear fixtures with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 586mm length and in a width of 58mm. Protection rating against dust and moisture: complete IP54. Protection rating of resistance to harmful mechanical impacts: IK08. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Microprismatic polycarbonate diffuser. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws.Pre-wiring of 35cm cable 3x1mm2. Accessory for serial installation, reference F3.L1.BRS.
31 78	Light source power: 11 W ▼ M ▼ Ø ▼LUX 98°
¹² <u>586</u> <u>586</u> <u>586</u> <u>586</u>	Luminaire connected power: 12.08 W Constant Current: 250 mA Light source luminous flux: 1760lm Luminaire luminous flux: 1198lm CRI: 90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 98° LOR: 68% Average Service Life: 50000h LED reliability: >60000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% 50% 70% Luminaire spacing = 0.45m Photobiological safety group: 1 Cd/KIm: 499 Luminaire efficiency: 99 lm/W Imax: 879 Cd This product contains a light source of energy efficiency class D Electronic Equipment S: On/Off D: DALI-2/switchDIM/corridorFUNCTION
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White Upgradeable, Replaceable, Repairable Image:

Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.04.2024]

CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15 T. + Pol. Ind. La Gavarra T. +

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com