

# BARIS 600

IP54 Wall mounted linear fixtures

ROVASI
Positive Lighting










## 661BRS.1-I725

IP54 | IK08 | 650º | +ELEC | +RAL

Wall mounted linear fixtures with symmetrical light distribution to achieve an effective task or general lighting.
Linear fixture in 568mm length and in a width of 44mm.
Protection rating against dust and moisture: complete IP54.
Protection rating of resistance to harmful mechanical impacts: IK08.
Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.
Microprismatic polycarbonate diffuser.
Highly efficient linear printed circuit board.
Built-in driver, included.
Electronic options for lighting control: DALI/DSI.
Passive temperature management.
Accessory for serial installation, reference F3.L6.BRS.

**Light source power:** 6 W
**Fixture power:** 7.1 W
**Constant Current:** 150 mA
**Luminous flux of the light source:** 1260lm
**Luminous flux of the fixture:** 855lm
**CRI:** 80
**Colour Temperature:** 4000K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 98º
**LOR:** 68%
**Average Service Life:** 50000h
**LED reliability:** >60000h L80B10
**UGR:** <19 under the below indicated parameters
Room dimensions X=4H/8H
Reflectance 20% | 50% | 70%
Luminaire spacing = 0.85m
**Photobiological safety group:** 1
**Cd/Klm:** 499
**Luminous efficacy:** 120 lm/W
**Imax:** 628 Cd
**This product contains a light source of energy efficiency class** C






| ▼M | ▼Ø | ▼LUX | 98° |
|---|---|---|---|
| 1 | 2.3 | 427 | |
| 2 | 4.6 | 107 | |
| 3 | 6.9 | 47 | |
| 4 | 9.2 | 27 | |
| 5 | 11.5 | 17.1 | |

**Electronic Equipment**
**S:** On/Off
**D:** DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

**Finishes**
**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

**Upgradeable, Replaceable, Repairable**



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

**5 years guarantee**

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**