GOWEL 100 IP20 Recessed linear downlights



	196GWL.1-I952
	IP20 IK06 650° +RAL IMAGE Image: state s
	Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear fixture in 1457mm length and in a width of 64mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
34 []65	Light source power: 23 W Imax=6036 Cd n=100.0% V M V Ø VLUX 90°
1457 1457 []84]84	Luminaire connected power: 27.05 W Constant Current: 150 mA Light source luminous flux: 3975lm Luminaire luminous flux: 3856lm CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: DASY° LOR: 97% Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1 Cd/KIm: 1547 Luminaire efficiency: 143 lm/W Imax: 6149 Cd This product contains a light source of energy efficiency class D
	Electronic Equipment S: On/Off SE: On/Off + 3h battery D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM+ 3 hours battery DE: DALI-3/switchDIM+ 3 hours battery
	DDE: DALI-2/switchDIM+ 3 hours battery (DALI) *Add the suffix -S, -SE, -D, -DE, -DDE after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.04.2024]

5 years guarantee **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com