# GOWEL 100 IP20 Recessed linear downlights



	191GWL.1-I727
	IP20 IK06 650° +RAL Image: Sea x 73mm Image: Se
	Recessed ceiling mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting. Linear fixture in 597mm length and in a width of 84mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. PMMA optic to achieve specific photometric results. Accessories available to create customized linear systems. Highly efficient linear printed circuit board. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
3+ <u>[</u> -]]65 597	Light source power: $9 \text{ W}$ Luminaire connected power: $11.84 \text{ W}$ Constant Current: $150 \text{ mA}$ Light source luminous flux: $1590\text{ lm}$ Luminaire luminous flux: $1542\text{ lm}$ CRI: $80$ Colour Temperature: $3000\text{K}$ Chromaticity Tolerance: MacAdam 3 Beam Angle: DASY° LOR: $97\%$
10 []84 597	Average Service Life: 50000h LED reliability: >54000h L80B10 Photobiological safety group: 1 Cd/KIm: 1547 Luminaire efficiency: 130 lm/W Imax: 2460 Cd This product contains a light source of energy efficiency class D
	Electronic Equipment S: On/Off D: DALI-2/switchDIM/corridorFUNCTION
	*Add the suffix <b>-S, -D</b> after the reference to indicate your electronic equipment choice. <b>Finishes</b> <b>2:</b> RAL9005: Jet Black, <b>4:</b> RAL7016: Anthracite Grey, <b>7:</b> RAL9006: White Aluminium, <b>1:</b> RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

# 5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.**

Spain

Pol. Ind. La Gavarra

#### Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13 08540 Centelles | Barcelona

info@rovasi.com www.rovasi.com