GOWEL 100 IP20 Recessed linear downlights



1	131GWL.1-I734
	IP20 IK06 650° +RAL Image: Size x 73mm Image: Size x 73mm Image: Size x 73mm Size x 73mm Size x 73mm Image: Size x 73mm Image: Size x 73mm Image: Size x 73mm
	Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting. Linear fixture in 597mm length and in a width of 84mm. Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request. Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board. Accessories available to create customized linear systems. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction modules in different ways to create customized systems.
3+ <u> </u>]65 597	Light source power: 9 W Luminaire connected power: 11.84 W Constant Current: 150 mA Light source luminous flux: 1710 lm Luminaire luminous flux: 1590 lm CRI: 80 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 65° LOR: 93% Average Service Life: $50000h$ LED reliability: >54000h L80B10 UGR: <19 Numeric Life Life: $5000h$ LED reliability: >54000h L80B10 UGR: <19
597	Photobiological safety group: 1 Cd/KIm: 804 Luminaire efficiency: 134 lm/W Imax: 1375 Cd This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off D: DALI-2/switchDIM/corridorFUNCTION
	*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]
5 years guarantee

 $-\frac{1}{2}(\text{LED})^{-1} \rightleftharpoons \frac{1}{2}(\text{LED})^{-1}$

CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com