## GOWEL 100 IP20 Recessed linear downlights



I	131GWL.1-I741
	IP20     IK06     650°     +RAL       Image: Size x 73mm     3.12Kg
	<ul> <li>Recessed ceiling mounted linear downlights with symmetrical light distribution to achieve an effective task or general lighting.</li> <li>Linear fixture in 597mm length and in a width of 84mm.</li> <li>Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.</li> <li>Range of PMMA optics to achieve specific photometric results.</li> <li>Highly efficient linear printed circuit board.</li> <li>Accessories available to create customized linear systems.</li> <li>Built-in driver, included.</li> <li>Electronic options for lighting control: DALI/DSI.</li> <li>Passive temperature management.</li> <li>Ceiling-mounted using steel support with screws.</li> <li>Pre-wiring of 35cm cable 3x1mm2.</li> <li>It is possible to combine different lengths and junction modules in different ways to create customized systems.</li> </ul>
3 <u>+</u> j00 597	Light source power: $9 \text{ W}$ Fixture power: $11.84 \text{ W}$ Constant Current: $150 \text{ mA}$ Luminous flux of the light source: $1740\text{ lm}$ Luminous flux of the fixture: $1618\text{ lm}$ CRI: $80$ Colour Temperature: $5000\text{K}$ Chromaticity Tolerance: MacAdam 3 Beam Angle: $65^{\circ}$ LOR: $93\%$ Average Service Life: $50000\text{h}$ LED reliability: >54000h L80B10
10 []84 ]84	UGR: <19 Photobiological safety group: 1 Cd/KIm: 804 Luminous efficacy: 137 lm/W Imax: 1399 Cd This product contains a light source of energy efficiency class C
	Electronic Equipment S: On/Off D: DALI-2/DSI switchDIM/corridorFUNCTION
	*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.
	Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White
	Upgradeable, Replaceable, Repairable

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

 $-\frac{1}{2}(\text{LED})^{-1} \rightleftharpoons \frac{1}{2}(\text{LED})^{-1}$ 

## 5 years guarantee E BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

## **ROVASI S.L.**

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

## Contact Ronda de la Font Grossa, 15

T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com