(`(IP20



OWEL 200) Frameless recessed li	lear downlights	SI
	D1GWL.1-I762 Image: Display the problem of the	
581 <u>]</u> 65	Light source power: 19 W Fixture power: 22.35 W Constant Current: 300 mA Luminous flux of the light source: 3330lm CRI: 80 Colour Temperature: 5000K	,

Imax=19242 Cd	η=100.0%	▼ M	٧Ø	▼LUX	17°
HAA	H	1	0.30	19242	
$\times \times 11$	00	2	0.61	4811	
	1500	3	0.91	2138	
1	000	4	1.21	1203	
$\land \lor \lor$	500	5	1.51	770	

Imax: 21146 Cd This product contains a light source of energy efficiency class C

Electronic Equipment S: On/Off

Beam Angle: 17° LOR: 91%

UGR: 19

Cd/Klm: 6350

70

581

D: DALI-2/switchDIM/corridorFUNCTION

Chromaticity Tolerance: MacAdam 3

Average Service Life: 50000h LED reliability: >54000h L80B10

Photobiological safety group: 1

Luminous efficacy: 136 lm/W

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

·

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.04.2024]

5 years guarantee BSI Cert ISO 9001:2015 - nºFM 39346

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

Ronda de la Font Grossa, 15

08540 Centelles | Barcelona

Contact T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com

BSI Cert ISO 14001:2015 - nºEMS 554685