GOWEL 200



| IP20 Frameless recessed linear downl | ights |
|--------------------------------------|-------|
| | |

| 1 | 231GWL.1-I727 | |
|-----------|--|--|
| | IP20 IK06 650° +RAL IP20 IK06 650° +RAL | 3.06Kg |
| | Recessed ceiling mounted linear downlights with symmetrask or general lighting. Frameless linear fixture in 581mm length and in a width of Powder painted extruded aluminium profile available in a Range of PMMA optics to achieve specific photometric of Highly efficient linear printed circuit board. Accessories available to create customized linear system Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management. Ceiling-mounted using steel support with screws. Pre-wiring of 35cm cable 3x1mm2. It is possible to combine different lengths and junction massive systems. | of 70mm. assorted finishes, customized RAL under request. results. ns. |
| <u> </u> | Light source power: 9 W Luminaire connected power: 11.84 W | Imax=1189 Cd η=100.0% ▼ M ▼ Ø ▼LUX 65° 1 1.28 1189 |
| 501 | Constant Current: 150 mA Light source luminous flux: 1590lm Luminaire luminous flux: 1479lm CRI: 80 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 65° LOR: 93% Average Service Life: 50000h LED reliability: >54000h L80B10 | 200 2 2.6 297 400 3 3.8 132 800 4 5.1 74 1000 5 6.4 48 |
| 4 []70 | UGR: <19 Photobiological safety group: 1 Cd/Klm: 804 | |
| 581 | Luminaire efficiency: 125 lm/W Imax: 1278 Cd | |
| | This product contains a light source of energy eff Electronic Equipment S: On/Off | nciency class D |
| | Convolution D: DALI-2/switchDIM/corridorFUNCTION *Add the suffix -S, -D after the reference to indicate your electronic | ic equipment choice |
| | Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL900 | |
| | Upgradeable, Replaceable, Repairable | |
| Note | | |

Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee CE BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Spain

Pol. Ind. La Gavarra

08540 Centelles | Barcelona

Contact Ronda de la Font Grossa, 15 T. +34 93 881 35 12 T. +34 93 881 37 13

info@rovasi.com www.rovasi.com