

391GWL.1-I748



Surface mounted linear downlights with asymmetrical light distribution to achieve an effective task or accent lighting.

Linear fixture in 581mm length and in a width of 70mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

PMMA optic to achieve specific photometric results.

Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted using cleats.

It is possible to combine different lengths and junction modules in different ways to create customized systems.

Light source power: 19 W

Luminaire connected power: 22.35 W

Constant Current: 300 mA

Light source luminous flux: 3050lm

Luminaire luminous flux: 2959lm

CRI: 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: DASY°

LOR: 97%

Average Service Life: 50000h

LED reliability: >54000h L80B10

Photobiological safety group: 1

Cd/Klm: 1547

Luminaire efficiency: 132 lm/W

Imax: 4718 Cd

This product contains a light source of energy efficiency class D

Electronic Equipment


S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION


*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White



Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com