
GOWEL 400

IP20 Pendant linear downlights









401GWL.1-I762









Pendant linear downlights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 581mm length and in a width of 70mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Range of PMMA optics to achieve specific photometric results. Highly efficient linear printed circuit board.

Accessories available to create customized linear systems.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling-mounted with adjustable steel wire suspension (1m) and transparent electrical wire. Different suspension length on request.

It is possible to combine different lengths and junction modules in different ways to create customized

max=19242 Cd

η=100.0% ▼M ▼Ø ▼LUX

2 0.61 4811

3

4 1.21 1203

0.30 19242

0.91 2138

1.51

Light source power: 19 W

Luminaire connected power: 22.35 W

Constant Current: 300 mA

Light source luminous flux: 3330lm Luminaire luminous flux: 3030lm

CRI: 80

Colour Temperature: 5000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17°

LOR: 91%

Average Service Life: 50000h LED reliability: >54000h L80B10

UGR: 19

Photobiological safety group: 1

Cd/Klm: 6350

Luminaire efficiency: 136 lm/W

Imax: 21146 Cd

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

T. +34 93 881 35 12

info@rovasi.com www.rovasi.com

T. +34 93 881 37 13