TIRET 800

IP40 Projectors



▼Ø ▼LUX

64 6.1

2.0 575

η=100.0% ▼ M

200

300

400

1


2 4.1 144


3

4 8.2 36

5 10.2 23 919







851TRT.1-I732



IP40 650°





Linear projectors or uplights with symmetrical light distribution to achieve an effective task or general

Linear fixture in 566mm length and in a width of 40mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

Opal extruded polycarbonate diffuser.

Highly efficient linear printed circuit board. Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Wall mounted by adjustable mounting brackets.

Matching products:

TIRET 100 recessed.

TIRET 200 frameless recessed.

TIRET 300 surface mounted.

TIRET 400 and TIRET 500 pendant.

TIRET 600 and TIRET 700 wall-mounted.

TIRET 800 projectors.

Light source power: 11 W Fixture power: 12.08 W Constant Current: 250 mA

Luminous flux of the light source: 2050lm Luminous flux of the fixture: 1292lm

CRI: 80

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 91° **LOR:** 63%

Average Service Life: 50000h LED reliability: >72000h L80B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.65m

Photobiological safety group: 1

Cd/Klm: 443

Luminous efficacy: 107 lm/W

Imax: 908 Cd

This product contains a light source of energy efficiency class C

Electronic Equipment

S: On/Off
D: DALI-2/switchDIM/corridorFUNCTION

*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASI S.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra 08540 Centelles | Barcelona Contact T. +34 93 881 35 12

info@rovasi.com

T. +34 93 881 37 13

www.rovasi.com