SATELLITE Surface mounted downlights







102STL.1-I863



Surface-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting. Neutral cylindrical body in diameter 190mm. Adjustable to 20° and 180°+180° rotation. Aluminium reflector in assorted finishes: specular metalized, facetted metalized or sandblasted metalized depending on the beam angle outcome. Powder painted aluminium body available in assorted finishes, customized RAL under request. Built-in driver, included. Electronic options for lighting control: DALI-2. Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself. Mounting to the ceiling plate with two securing points. Cable entry from the top of the fixture. SATELLITE can be combined with the BASE surface mounted line to get a harmonious finish. Light source power: 11 W Imax=7017 Cd η=90.9% ▼M ▼Ø ▼LUX 24° Luminaire connected power: 12.61 W 1 0.42 7017 Constant Current: 350 mA 2 0.85 1754 2000 Light source luminous flux: 1960lm 3000 Luminaire luminous flux: 1784lm 1.27 780 3 4000 **CRI:** >80 5000 4 1.69 439 Colour Temperature: 2700K Chromaticity Tolerance: MacAdam 3 5 2.1 281 Beam Angle: 24° LOR: 91% Average Service Life: 50000h LED reliability: 50000h L90B10 **UGR:** <16 Photobiological safety group: 1 Cd/Klm: 3580 Luminaire efficiency: 141 lm/W Imax: 7017 Cd This product contains a light source of energy efficiency class D **Electronic Equipment** S: On/Off D: DALI-2/switchDIM/corridorFUNCTION *Add the suffix -S, -D after the reference to indicate your electronic equipment choice. Finishes 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

T. +34 93 881 35 12 T. +34 93 881 37 13

Contact

info@rovasi.com www.rovasi.com