
# GOWEL 800

# **IP20 Projectors**







# 801GWL.1-I769



IP20







Linear projectors with symmetrical light distribution to achieve an effective task or general lighting.

Linear fixture in 581mm length and in a width of 70mm.

Powder painted extruded aluminium profile available in assorted finishes, customized RAL under request.

max=28260 Cd

16500

η=100.0% ▼M ▼Ø ▼LUX

2 0.61 7065

3

4 1.21 1766

0.30 28260

0.91 3140

1.51

Range of PMMA optics to achieve specific photometric results.

Highly efficient linear printed circuit board.

Built-in driver, included.

Electronic options for lighting control: DALI-2.

Passive temperature management.

Ceiling or wall mounted using adjustable supports.

Matching products:

GOWEL 100 recessed with frame. GOWEL 200 frameless recessed. GOWEL 300 surface mounted. GOWEL 400 pendant.

Light source power: 32 W Fixture power: 36.36 W Constant Current: 500 mA

Luminous flux of the light source: 4890lm Luminous flux of the fixture: 4450lm

**CRI:** 80

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17°

**LOR:** 91%

Average Service Life: 50000h LED reliability: >54000h L80B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H

Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1

Cd/Klm: 6350

Luminous efficacy: 122 lm/W

Imax: 31052 Cd

This product contains a light source of energy efficiency class D

## **Electronic Equipment**

S: On/Off

D: DALI-2/switchDIM/corridorFUNCTION

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

#### **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

#### **ROVASI S.L.**

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com

Contact

www.rovasi.com