
# CHESS Trimless downlights







## 107CXS.1-R1082



Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or general lighting.

Square frameless design for plasterboard ceilings available in 60mm x 60mm.

Powder painted body available in assorted finishes, customized RAL under request. To complete the effect of this luminaire, it is suggested that the interior be painted the same RAL colour

as the ceiling.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].


Remote driver included.

Electronic options for lighting control: DALI-2.

3 hours battery available as option\*.

Passive temperature management: heat dissipation flows through aluminium heat sink diffuser. Mounted to the ceiling by two fixing points with screws.

Light source power: 8.5 W Luminaire connected power: 9.41 W Constant Current: 250 mA Light source luminous flux: 1110lm Luminaire luminous flux: 755lm **CRI:** >90 Colour Temperature: 3000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 17° LOR: 68% Average Service Life: 50000h LED reliability: >53000h L80B50 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.6m



Photobiological safety group: 1 Luminaire efficiency: 80 lm/W This product contains a light source of energy efficiency class E

## Electronic Equipment

S: On/Off D: DALI-2/switchDIM

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

5 years guarantee

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

## **CE** BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

### ROVASI S.L.

Pol. Ind. La Gavarra

Spain

08540 Centelles | Barcelona

Ronda de la Font Grossa, 15

#### Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com