# Minidownlights



η=100.0% ▼ M ▼ Ø ▼LUX

0.31 3832

239 1.23 4


0.61 958

1.53 153

1

3 0.92





## 110TNS.1-R1081



IP20 850°











Imax=3832 Cd

Recessed ceiling-mounted downlights with symmetrical light distribution to achieve an effective task or ambient lighting.

Round design in diameter 55mm.

Aluminium trim powder painted in various finishes, customized RAL under request.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0035].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0035].

Remote driver included.

Passive temperature management: heat dissipation via aluminium heat sink.

Ceiling-mounted using galvanised steel support with spring clamps.

Light source power: 8.5 W Luminaire connected power: 9.41 W Constant Current: 250 mA Light source luminous flux: 1085lm Luminaire luminous flux: 738lm

**CRI:** >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 17°

**LOR:** 68%

Average Service Life: 50000h LED reliability: >53000h L80B50

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.6m

Photobiological safety group: 1 Luminaire efficiency: 78 lm/W

This product contains a light source of energy efficiency class E

### **Electronic Equipment**

S: On/Off
D: DALI-2/switchDIM

\*Add the suffix -S, -D after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 27.04.2024]

5 years guarantee



Spain