
# KORAMU 300

Two sides light emission IP66 bollards

ROVASI
Positive Lighting







## 320KRM.4-I730

IP66 | IK10 | 850º | +RAL

Bollard with two sides light emission, symmetrical distribution.
Bollard height 675mm.
Protection rating against dust and moisture: IP66 – full protection.
Protection rating for resistance against harmful mechanical impacts: IK10.
Extruded aluminium profile coated with polyester powder along with C4 treatment for corrosion resistance to guarantee further durability. Textured paint finish. Different RAL colour finishes available under request. C5-M special coating for highly corrosive environments is available under request.
4mm frontal polycarbonate diffuser.
Interior opal diffuser.
Anticondensation device.
Silicone gasket.
Highly efficient linear printed circuit board.
Built-in driver, included. Ambient temperature: up to 50ºC.
Electronic options for light control: DALI/DSI.
A4 stainless steel locking screw. Optional supply of A2 stainless steel vandal-resistant screws.
IP68 connector not included, it can be ordered separately: F3.A3 (On/Off) / F3.A5 (DALI).
Pre-wiring of 35cm cable 3x1mm2.
Mounting plate for floor installation supplied with the fixture.
Accessory for concrete installation reference F3.P2.KRM.
Accessory for grass installation reference F3.O2.KRM.

**Light source power:** 2x11 W
**Fixture power:** =12.08*2 W
**Constant Current:** 250 mA
**Luminous flux of the light source:** 2x1900lm
**Luminous flux of the fixture:** 2x855lm
**CRI:** 80
**Colour Temperature:** 2700K
**Chromaticity Tolerance:** MacAdam 3
**Beam Angle:** 91°
**LOR:** 45%
**Average Service Life:** 50000h
**LED reliability:** >60000h L80B10
**Photobiological safety group:** 1
**Luminous efficacy:** 35 lm/W
**This product contains a light source of energy effic**





### Electronic Equipment


**S:** On/Off
**D:** DALI-2/DSI/switchDIM
There are accessories available for dimming devices.
*Add the suffix **-S, -D** after the reference to indicate your electronic equipment choice.

### Finishes

**1:** RAL9010: Pure White textured, **2:** RAL9005: Jet Black textured, **4:** RAL7016: Anthracite Grey textured, **7:** RAL9006: White Aluminium textured

### Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 29.03.2024]

**5 years guarantee**

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

**ROVASI S.L.**
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

**Contact**
T. +34 93 881 35 12
T. +34 93 881 37 13
info@rovasi.com
**www.rovasi.com**