SEAI

IP65 Small recessed downlights



20°

η=100.0% ▼ M ▼ Ø ▼ LUX

1

3

4

0.36 5011


0.72 1253

1.07 557

1.43 313

1.79 200





124SEL.1.01-R1096



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accept

Imax=5011 Cd

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation.

Light source power: 15.4 W Fixture power: 17.05 W Constant Current: 450 mA

Luminous flux of the light source: 1960lm Luminous flux of the fixture: 1333lm

CRI: >90

Colour Temperature: 2700K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 20°

LOR: 68%

Average Service Life: 50000h LED reliability: 50.000h L90B10

UGR: <19 under the below indicated parameters

Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3m

Photobiological safety group: 1 Luminous efficacy: 78 lm/W

Electronic Equipment

S: On/Off (AC/DC)

K: On/Off (basic)

D: DALI-2/DSI/switchDIM/corridorFUNCTION

B: Bluetooth-Casambi

SE: On/Off (AC/DC) + 3 hours battery (class I)(embedding diameter battery >84mm)

DE: DALI-2/DSI/switchDIM/corridorFUNCTION + 3 hours battery (class I)(embedding diameter battery >84mm)

There are accessories available for dimming devices.

*Add the suffix -S, -K, -D, -B, -SE, -DE after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, 2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

5 years guarantee

