
SEAL IP65 Small recessed downlights






124SEL.1.01-R1098



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent.

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation.

Light source power: 15.4 W Fixture power: 17.05 W Constant Current: 450 mA Luminous flux of the light source: 2225lm Luminous flux of the fixture: 1513lm **CRI:** >90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 20° LOR: 68% Average Service Life: 50000h LED reliability: 50.000h L90B10 UGR: <19 under the below indicated parameters Room dimensions X=4H/8H Reflectance 20% | 50% | 70% Luminaire spacing = 0.3mPhotobiological safety group: 1 Luminous efficacy: 89 lm/W



This product contains a light source of energy efficiency class E

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC) SE: On/Off (AC/DC) + Battery 3h D: DALI-2/DSI switchDIM/corridorFUNCTION DE: DALI-2/DSI switchDIM + 3h battery B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 18.04.2024]

Spain

5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L. Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

