



101BSQ.1-R526



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Square design with frameless appearance in 96mm x 96mm.

Aluminium body and interior frame powder painted in assorted finishes, customized RAL under request. To complete the effect of this fixture, it is suggested that the interior frame be painted the same RAL colour as the ceiling.

Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0096].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI-2.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation.

Light source power: 5 W

Luminaire connected power: 5.66 W

Constant Current: 150 mA

Light source luminous flux: 520lm

Luminaire luminous flux: 520lm

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 36°

LOR: 100%

Average Service Life: 50000h

LED reliability: >50000h L70B50

UGR: <16


Photobiological safety group: 1

Cd/Klm: 2100

Luminaire efficiency: 92 lm/W

Imax: 1092 Cd

This product contains a light source of energy efficiency class F

**Electronic Equipment**

K: On/Off (basic)

S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h

D: DALI-2/switchDIM/corridorFUNCTION

DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

*Add the suffix **-K, -S, -SE, -D, -DE, -B** after the reference to indicate your electronic equipment choice.

Finishes

2: RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium, **1:** RAL9010: Pure White

Upgradeable, Replaceable, Repairable**Note**

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 26.04.2024]

5 years guarantee

BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

ROVASI S.L.

Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact

T. +34 93 881 35 12
T. +34 93 881 37 13

info@rovasi.com

www.rovasi.com