

# CONICAL

## Small recessed downlights









### 101CNC.1-R524



IP20











Imax=1939 Cd





η=100.0% ▼ M ▼ Ø ▼LUX

1

2

3 1.12

4 1.49 121

5 1.87

0.37 1939

78

0.75 485 21°

Recessed ceiling-mounted small downlight with symmetrical light distribution to achieve an effective task or general lighting.

Circular design in diameter 85mm.

850°

Powder painted aluminium conical trim available in assorted finishes, customized RAL under request. Accessory available to increase the protection rating to IP44 from underneath [reference M2.H0085].

Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI/DSI.

3 hours battery available as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink diffuser.

Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

Light source power: 5 W Fixture power: 5.66 W Constant Current: 150 mA

Luminous flux of the light source: 560lm Luminous flux of the fixture: 487lm

**CRI:** >90

Colour Temperature: 4000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 21° **LOR:** 87%

Average Service Life: 50000h LED reliability: >50000h L70B50

**UGR:** <16

Photobiological safety group: 1 Luminous efficacy: 86 lm/W

This product contains a light source of energy efficiency class F

#### **Electronic Equipment**

K: On/Off (basic)
S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/DSI switchDIM/corridorFUNCTION
DE: DALI-2/DSI switchDIM + 3h battery

B: Bluetooth-Casambi

## **Finishes**

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 20.04.2024]

5 years guarantee



Spain

T. +34 93 881 37 13

<sup>\*</sup>Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.