

Minidownlights









101TKN.1-R526













lmax=1093 Co







η=100.0% ▼ M

1

2 1.30 273

3 1.95 121

4 2.6 68

▼Ø ▼LUX

0.65 1091

3.2 44

Recessed ceiling-mounted small downlights with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Circular design in diameter 70mm.

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0070]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050].

Remote driver included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.

Light source power: 5 W Fixture power: 5.66 W Constant Current: 150 mA

Luminous flux of the light source: 520lm Luminous flux of the fixture: 520lm

CRI: >90

Colour Temperature: 3000K

Chromaticity Tolerance: MacAdam 3

Beam Angle: 36° **LOR:** 100%

Average Service Life: 50000h LED reliability: >50000h L70B50

UGR: <16

Photobiological safety group: 1

Cd/Klm: 2100

Luminous efficacy: 92 lm/W

Imax: 1092 Cd

This product contains a light source of energy efficiency class F

Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC)

SE: On/Off (AC/DC) + Battery 3h
D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM + 3h battery

B: Bluetooth-Casambi

*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

Upgradeable, Replaceable, Repairable





Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 23.04.2024]

5 years guarantee



BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685 **ROVASIS.L.**

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com

08540 Centelles | Barcelona