

# 101TKN.1-R527



Recessed ceiling-mounted small downlights with symmetrical light distribution to achieve an effective task, accent or ambient lighting.

Circular design in diameter 70mm.


Light source power: 5 W

Fixture power: 5.66 W

Powder painted die-cast aluminium trim available in assorted finishes, customized RAL under request. Accessory available to increase the protection rating to IP44 from underneath [reference M2.A0070]. Honeycomb anti-dazzle screen accessory to increase visual comfort [reference M6.A0050]. Remote driver included.

Electronic options for lighting control: DALI-2.

Passive temperature management: heat dissipation flows through an aluminium heat sink. Ceiling-mounted by spring clamps for easy installation, ceiling thickness up to 25mm.



Constant Current: 150 mA Luminous flux of the light source: 560lm Luminous flux of the fixture: 560lm CRI: >90 Colour Temperature: 4000K Chromaticity Tolerance: MacAdam 3 Beam Angle: 36° LOR: 100% Average Service Life: 50000h LED reliability: >50000h L70B50 UGR: <16 Photobiological safety group: 1

Cd/Klm: 2031 Luminous efficacy: 99 lm/W Imax: 1137 Cd

This product contains a light source of energy efficiency class  $\ensuremath{\,\mathsf{F}}$ 

### Electronic Equipment

K: On/Off (basic) S: On/Off (AC/DC) SE: On/Off (AC/DC) + Battery 3h D: DALI-2/switchDIM/corridorFUNCTION DE: DALI-2/switchDIM + 3h battery B: Bluetooth-Casambi

\*Add the suffix -K, -S, -SE, -D, -DE, -B after the reference to indicate your electronic equipment choice.

#### Finishes

2: RAL9005: Jet Black, 4: RAL7016: Anthracite Grey, 7: RAL9006: White Aluminium, 1: RAL9010: Pure White

#### Upgradeable, Replaceable, Repairable



#### Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 25.04.2024]

# 5 years guarantee

BSI Cert ISO 9001:2015 - nºFM 39346 BSI Cert ISO 14001:2015 - nºEMS 554685

# ROVASI S.L.

Spain

Ronda de la Font Grossa, 15 Pol. Ind. La Gavarra

08540 Centelles | Barcelona

# Contact

T. +34 93 881 35 12 T. +34 93 881 37 13 info@rovasi.com www.rovasi.com