


## 101BSM.1-R634



Recessed ceiling-mounted downlight with symmetrical light distribution to achieve an effective task, accent.

Emergency kit as option.

Passive temperature management: heat dissipation flows through an aluminium heat sink.

Ceiling-mounted with spring clamps for easy installation.

**Light source power:** 6.6 W

**Fixture power:** 7.69 W

**Constant Current:** 200 mA

**Luminous flux of the light source:** 670lm

**Luminous flux of the fixture:** 670lm

**CRI:** >90

**Colour Temperature:** 3000K

**Chromaticity Tolerance:** MacAdam 3

**Beam Angle:** 36°

**LOR:** 100%

**Average Service Life:** 50000h

**LED reliability:** >50000h L70B50

**UGR:** <19


**Photobiological safety group:** 1

**Cd/Klm:** 2100

**Luminous efficacy:** 87 lm/W

**Imax:** 1407 Cd

**This product contains a light source of energy efficiency class F**



## Electronic Equipment

**S:** On/Off (AC/DC)

**K:** On/Off (basic)

**D:** DALI-2/DSI/switchDIM/corridorFUNCTION

**B:** Bluetooth-Casambi

**SE:** On/Off (AC/DC) + 3 hours battery (class I)(embedding diameter battery >84mm)

**DE:** DALI-2/DSI/switchDIM/corridorFUNCTION + 3 hours battery (class I)(embedding diameter battery >84mm)


There are accessories available for dimming devices.

\*Add the suffix **-S, -K, -D, -B, -SE, -DE** after the reference to indicate your electronic equipment choice.

## Finishes

**1:** RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

## Upgradeable, Replaceable, Repairable



## Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

**5 years guarantee**



BSI Cert ISO 9001:2015 - n°FM 39346

BSI Cert ISO 14001:2015 - n°EMS 554685

## ROVASI S.L.

Ronda de la Font Grossa, 15  
Pol. Ind. La Gavarrà  
08540 Centelles | Barcelona  
Spain

## Contact

T. +34 93 881 35 12  
T. +34 93 881 37 13

info@rovasi.com  
[www.rovasi.com](http://www.rovasi.com)