
GRAVITY EVOLUTION

Pendant downlights

ROVASI
Positive Lighting






101GVE.1-I863



Pendant downlight with symmetrical light distribution to achieve an effective task, accent or ambient lighting.
Neutral cylindrical body in diameter 150mm.
Double Aluminium reflectors in assorted finishes. Top reflector: facetted metalized or sandblasted metalized depending on the beam angle outcome. Bottom reflector: sandblasted metalized.
Powder painted aluminium body available in assorted finishes, customized RAL under request.
Flush glass accessory available [reference M2.L0150]. Complete IP54 | IK05 fixture by ordering flush glass and IP rated connector accessories [reference F3.A3 (On/Off) / F3.A5 (DALI)].
Drop glass disk accessory available in assorted colours [reference M1.A0150].
Drop metal disk accessory available in assorted colours [reference M1.B0150].
Built-in driver, included.
Passive temperature management: heat dissipation flows through an aluminium heat sink and the fixture body itself.
Suspended 1 meter by three steel cords. Transparent electrical wire.
Mounted to the ceiling by cylindrical ceiling rose.
For a more dynamic result, it can be supplied with an adapter for three-phase track [accessory reference M3.A].
GRAVITY can be combined with the BASE surface-mounted line to achieve a uniform effect.

Light source power: 11 W
Fixture power: 12.61 W
Constant Current: 350 mA
Luminous flux of the light source: 1960lm
Luminous flux of the fixture: 1784lm
CRI: >80
Colour Temperature: 2700K
Chromaticity Tolerance: MacAdam 3
Beam Angle: 12º
LOR: 91%
Average Service Life: 50000h
LED reliability: 50000h L90B10
UGR: <16
Photobiological safety group: 1
Cd/Klm: 9093
Luminous efficacy: 141 lm/W
Imax: 17822 Cd
This product contains a light source of energy efficiency class D



▼M	▼Ø	▼LUX	12º
1	0.22	17823	
2	0.43	4456	
3	0.65	1980	
4	0.86	1114	
5	1.08	713	


Electronic Equipment

S: On/Off
SE: On/Off + 3 hours battery [class I][Battery embedding diameter: 84mm]
D: DALI-2/DSI/switchDIM
DE: DALI-2/DSI/switchDIM+3 hours battery [class I][Battery embedding diameter: 84mm]
DDE: DALI-2/DSI/switchDIM+3 hours battery (DALI) [class I][Battery embedding diameter: 84mm]
B: Bluetooth Casambi
There are available accessories for dimming devices.
*Add the suffix **-S, -SE, -D, -DE, -DDE, -B** after the reference to indicate your electronic equipment choice.

Finishes

1: RAL9010: Pure White, **2:** RAL9005: Jet Black, **4:** RAL7016: Anthracite Grey, **7:** RAL9006: White Aluminium

Upgradeable, Replaceable, Repairable



Note

LED technology and performance data are constantly changing. Current details should therefore be checked with ROVASI in order to ensure that it is still the most up to date reference. Updated data will be supplied on request. [Last revised on 28.03.2024]

5 years guarantee

EAC CE

BSI Cert ISO 9001:2015 - nºFM 39346
BSI Cert ISO 14001:2015 - nºEMS 554685

ROVASI S.L.
Ronda de la Font Grossa, 15
Pol. Ind. La Gavarra
08540 Centelles | Barcelona
Spain

Contact
T. +34 93 881 35 12 info@rovasi.com
T. +34 93 881 37 13 **www.rovasi.com**